

Please insert the following on page 30, at line 7:

What is claimed is:

### III. CLAIM AMENDMENTS

1. (Original) Device for producing any desired portions (6) and formats (5) of products (2), comprising an aligning belt (1) which conveys the products (2) and at a transfer edge (4) transfers them to a portioning belt (3) on which the portions (6) and the formats (5) are produced and with which the products are conveyed onwards as corresponding portions (6) and in the respective format (5), characterised in that the position of the transfer edge (4) can be changed by a drive relative to the portioning belt (3), at least in one direction (7,8) and/or the position of the portioning belt (3) can be changed by a drive relative to the transfer edge, at least in one direction (9,10), the position of the transfer edge (4) and the movement of the portioning belt (3) are co-ordinated with one another such that any desired portions (6) and formats (5) can be produced with the products, it comprises a detection means which transfers first data on the position of the respective product on the aligning belt (1) to a controller which also receives second data from the drives, the exact location of the respective product within the device can be calculated using the data and the controller controls the drives according to the desired portions and formats.
2. (Original) Device according to claim 1, characterised in that the position of the transfer edge (4) can be changed in and counter to the conveying direction (11) of the aligning belt (1), in that the portioning belt (3) is movable relative to the transfer edge (4) in one direction (10), and in that the angle between the conveying direction

(11) and the direction of movement (10) of the portioning belt is preferably 90° or 270°.

3. (Original) Device according to claim 1, characterised in that the position of the transfer edge (4) in the conveying direction (11) and transversely to the conveying direction (11) of the aligning belt (1) can be changed as desired.
4. (Original) Device according to claim 1, characterised in that the portioning belt (3) is constructed so as to be movable, at least in two directions (9,10) which are preferably perpendicular to one another.
5. (Original) Device according to claim 1, characterized in that the position of the transfer edge (4) can be changed in and counter to the conveying direction (11) of the aligning belt (1), and in that it comprises a means (12) with which the products can be lined up on the aligning belt (1) relative to the central track (13).
6. (Currently Amended) Device according to ~~any one of the preceding claims~~ claim 1, characterised in that it comprises a plurality of aligning belts (1) and/or a plurality of portioning belts (3).
7. (Original) Device according to claim 6, characterised in that the conveying direction (11,14) of the aligning belts (1) and/or of the portioning belts (3) is the same and/or or opposed.
8. (Currently Amended) Device according to ~~any one of the preceding claims~~ claim 1, characterised in that the

transfer edge (4) is displaceably mounted on the aligning belt (1) and displacement preferably takes place via a servomotor.

9. (Currently Amended) Device according to ~~any one of the preceding claims~~ claim 1, that the end (15) of the portioning belt (3) is displaceably mounted and displacement preferably takes place via a servomotor.
10. (Currently Amended) Device according to ~~any one of the preceding claims~~ claim 1, characterised in that the aligning belt (1) and/or the portioning belt (3) is/are driven by a servomotor.
11. (Currently Amended) Device according to ~~any one of the preceding claims~~ claim 1, characterised in that the desired portion patterns and the formats may be freely programmed and stored.
12. (Currently Amended) Device according to ~~any one of the preceding claims~~ claim 1, characterised in that the speed of the aligning belt is constant.
13. (Currently Amended) Device according to ~~any one of the preceding claims~~ claim 1, characterised in that the portioning belt (3) is also a loading belt.
14. (Currently Amended) System comprising a device according to ~~any one of claims 1 to 13~~ claim 1 and a packaging machine (16), wherein the portioning belt (3) is also a loading belt which places the portions in packaging cavities which

are conveyed along the packaging machine preferably in a clocked manner.

15. (Original) System according to claim 14, characterised in that the portioning belt (3) is arranged at a right angle to the packaging machine.
16. (Currently Amended) System according to ~~either claim 14 or 15~~ claim 14, characterised in that the aligning belt is arranged at a right angle to the portioning belt (3).
17. (Currently Amended) System according to ~~any one of claims 14 to 16~~ claim 1, characterised in that the device is coordinated with the clocking of the packaging machine.
18. (Original) Method for producing any desired portions (6) and formats (5) or products (2), comprising an aligning belt (1) which conveys the products (2) and transfers them at a transfer edge (4) to a portioning belt (3) on which the portions (6) and the formats (5) are produced and with which the products are conveyed onwards as a corresponding portion (6) and in the respective format (5), characterised in that the position of the transfer edge (4) relative to the portioning belt (3) is changed, in at least one direction and (7,8) and/or the position of the portioning belt (3) is moved relative to the transfer edge, at least in one direction (9,10) and the position of the transfer edge (4) and the movement of the portioning belt (3) are coordinated with one another such that any desired portions (6) and formats (5) are produced with the products, and the products are placed in a packaging in a clocked manner by the portioning belt.

19. (Original) Method according to claim 18, characterised in that the position of the transfer edge (4) is changed in and counter to the conveying direction (11) of the aligning belt (1), in that the portioning belt (3) is moved relative to the transfer edge (4) in one direction (10), and in that the angle between the conveying direction (11) and the direction of movement (10) of the portioning belt is preferably 90° or 270°.
20. (Original) Method according to claim 18, characterised in that the position of the transfer edge (4) in the conveying direction (11) and transversely to the conveying direction (11) of the aligning belt (1) is changed as desired.
21. (Original) Method according to claim 18, characterised in that the portioning belt (3) is moved at least in two directions (9,10) which are preferably perpendicular to one another.
22. (Original) Method according to claim 18, characterised in that the position of the transfer edge (4) is changed in the conveying direction (11) of the aligning belt (1), and in that the products on the aligning belt (1) are each positioned in a specific position relative to the central track (13) on the aligning belt (1).
23. (Currently Amended) Method according to ~~any one of claims 18 to 22~~ claim 18, characterised in that the transfer edge (4) is displaced relative to the aligning belt (1), preferably by a servomotor.

24. (Currently Amended) Method according to ~~any one of claims 18 to 23~~ claim 18, characterised in that the position of the products on the aligning belt (1) is detected, at least in the conveying direction (11), via a single detection means.
25. (Currently Amended) Method to ~~any one of claims 18 to 24~~ claim 18, characterised in that it is controlled by a controller in which at least one amount for the clocking of the portion in belt is stored.
26. (Original) Method according to claim 25, characterised in that the controller generates a signal for clocking at the drive of the portioning belt when the row of the format is complete.
27. (Currently Amended) Method according to ~~any one of claims 18 to 26~~ claim 18, characterised in that the speed of the aligning belt is constant.